

730S/D-S3S3

730S/D-F4S3

**3U SAS-SAS/FC-SAS Redundant RAID
Subsystem**



The 730 series RAID subsystem features 3Gb SAS or 4Gb FC-AL host performance to increase system efficiency and performance. It features high capacity expansion, with 16 hot-swappable SAS/SATA II hard disk drive bays in a 19-inch 3U rackmount unit, scaling to a maximum storage capacity in the terabyte range. The 730D series also supports dual controllers which provide better fault tolerance and higher reliability of system operation.

Exceptional Manageability

- ⦿ The firmware-embedded Web Browser-based RAID manager allows local or remote management and configuration
- ⦿ The firmware-embedded SMTP manager monitors all system events and user notification automatically
- ⦿ The firmware-embedded SNMP agent allows remote to monitor events via LAN with no SNMP agent required
- ⦿ Menu-driven front panel display
- ⦿ Innovative Modular architecture

Feature

- ⦿ Supports dual controller for features redundant RAID
- ⦿ Supports RAID levels 0, 1, 0+1, 3, 5, 6, 30, 50, 60 and JBOD
- ⦿ Supports online Array roaming
- ⦿ Online RAID level/stripe size migration
- ⦿ Online capacity expansion and RAID level migration simultaneously
- ⦿ Online Volume Set Expansion
- ⦿ Supports multiple array enclosures per host connection
- ⦿ Supports greater than 2TB per volume set
- ⦿ Supports up to 128 LUNs
- ⦿ Transparent data protection for all popular operating systems
- ⦿ RAID ADG provides the highest level of data protection
- ⦿ Instant availability and background initialization
- ⦿ Supports S.M.A.R.T, NCQ and OOB Staggered Spin-up capable drives
- ⦿ Local audible event notification alarm

- ⊙ Supports password protection
- ⊙ Serial port interface for remote event notification
- ⊙ Redundant flash image for high availability
- ⊙ Support spin down drives when not in use to extend service (MAID)
- ⊙ Supports Bad Blocks auto remapping and schedule volume check
- ⊙ Redundant active-active controller functionality ensures zero downtime or data loss
- ⊙ Fully redundant with hot swappable Controller, disks, cooling fans and power supplies
- ⊙ Supports hot spare and automatic hot rebuild

Series Technical Specifications

Model	730S/D-S3S3	730S/D-F4S3
RAID Controller	SAS-SAS	FC-SAS
Controller	Single or Redundant	Single or Redundant
Host Interface	Two 4x mini SAS (3Gb/s)	Two FC-AL (4 Gb/s)
Disk Interface	SAS 3Gb or SATA II	SAS 3Gb or SATA II
SAS expander	4x mini SAS (3Gb/s)	4x mini SAS (3Gb/s)
Capacity		
- Direct Attached	16 Disks	16 Disks
- Expansion	Up to 112 Disks	Up to 112 Disks
Processor Type	Intel IOP341 64-bit	Intel IOP341 64-bit
Cache Memory	512MB ~ 4GB DDR-II ECC SDRAM	512MB ~ 4GB DDR-II ECC SDRAM
Battery Backup	Optional	Optional
Management Port support	Yes	Yes
Monitor Port support	Yes	Yes
RAID Features		
RAID level	0, 1, 0+1, 3, 5, 6, 30, 50, 60 and JBOD	0, 1, 0+1, 3, 5, 6, 30, 50, 60 and JBOD
Array Group	Up to 128	Up to 128
LUNs	Up to 128	Up to 128
Hot Spare	Yes	Yes
Drive Roaming	Yes	Yes
Online Rebuild	Yes	Yes

Variable Stripe Size	Yes	Yes
E-mail Notification	Yes	Yes
Online capacity expansion, RAID level /stripe size migration	Yes	Yes
Online Array roaming	Yes	Yes
Online consistency check	Yes	Yes
SMTP manager and SNMP agent	Yes	Yes
Redundant Flash image	Yes	Yes
Instant availability and background initialization	Yes	Yes
S.M.A.R.T. support	Yes	Yes
MAID	Yes	Yes
Bad block auto-remapping	Yes	Yes
Enclosure		
Platform	Rackmount	Rackmount
Form Factor	3U	3U
# of Hot Swap Trays	16	16
Tray Lock	Yes	Yes
Disk Status Indicator	Access / Fail LED	Access / Fail LED
Backplane	SAS / SATA II Single BP	SAS / SATA II Single BP
# of PS/Fan Modules	500W x 2 w/PFC	500W x 2 w/PFC
# of Fans	4	4
Power requirements	AC 90V ~ 264V Full Range 10A ~ 5A, 47Hz ~ 63Hz	AC 90V ~ 264V Full Range 10A ~ 5A, 47Hz ~ 63Hz
Environmental		
Relative Humidity	10% ~ 85% Non-condensing	10% ~ 85% Non-condensing
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)	10°C ~ 40°C (50°F ~ 104°F)
Physical Dimension	590(L) x 482 (W) x 131(H) mm	590(L) x 482 (W) x 131(H) mm
Weight (Without Disk)	24 / 25 Kg	24 / 25 Kg

Specification is subject to change without notice. All company and product names are trademarks of their respective owners.